

autovictor

 *Keep on moving to the future.*

AERIAL PLATFORM

HAULOTTE HA 20 RTJ



HA20 RTJ HA20 RTJ PRO



MAXIMUM PRODUCTIVITY

- > 360° continuous rotation (PRO model only)
- > 4 wheel steering for more agility (PRO model only)

EXCELLENT ROUGH-TERRAIN CAPABILITIES

- > Climbing ramps up to 45%
- > Oscillating axle for a very good ground grip (PRO model)
- > Differential lock (hydraulic) to optimize crossing capacity

OPTIMIZED COST OF OWNERSHIP

- > Simplified hydraulic architecture thanks to mechanical axles
- > Simple and reliable engine (>19kW, does not require a particulate filter)
- > Sherpal ready for maximized usage and to generate additional revenue (optional)

OPTIMAL SAFETY

- > Haulotte Activ'Shield Bar: anti-crushing system (standard PRO model)
- > Haulotte Activ'Lighting System: load and unload the machine in low visibility conditions (standard PRO model)


HA20 RTJ

HA20 RTJ PRO

ROUGH TERRAIN ARTICULATING BOOMS

TECHNICAL DATA

	HA20 RTJ	HA20 RTJ PRO
Working height	20.5 m	
Platform height	18.5 m	
Horizontal outreach	11.9 m	
Tailswing	42 cm	
A Length - stowed	8.60 m	
B Width	2.43 m	
C Storage / transport height	2.98 m	
D Wheelbase	2.5 m	
E Ground clearance - mini	30 cm	
E Ground clearance - maxi	36 cm	
F x G Platform size	1.80 x 0.8 m	
H Storage / transport length	6.16 m	
Tilt	4° - option 6°	
Platform rotation	180° (+90° / -90°)	
Turntable rotation	355° non continuous	360° continuous
Up and over clearance	8.5 m	
Height - stowed	2.47 m	
Lift capacity	250 kg (2 pers.) - option 350 kg	
Drive speed	0.5 - 5 km/h	
Maximum wind speed rating	45 km/h	
Gradeability	45 %	
Tires - solid rough terrain	910 x 355 mm	
Turning radius - outside	5,2 m	
Power source	KUBOTA, TIER 4 final : Stage V, China IV, Diesel: 18.5 kW	
Weight	9 180kg	9 430kg




STANDARD EQUIPMENT

- > Haulotte Activ'Shield Bar (standard PRO model)
- > Haulotte Activ'Lighting System (standard PRO model)
- > Haulotte Stop Emission System
- > Haulotte Activ'Screen
- > 4 wheel drive and 4 wheel steering (standard PRO model) / 4 wheel drive and 2 wheel steering (standard RTJ model)
- > Permanent limited slip differential
- > Oscillating axle (PRO model only)
- > 360° continuous rotation (PRO model only)
- > Simultaneous and proportional movements
- > Modular standard basket
- > Swing out engine tray for ease of maintenance
- > Access to the MyHaulotte multi-service portal
- > Universal telematic plug
- > 12 V battery / electrical control system
- > Rotating beacon
- > Upper control box protection cover

OPTIONS AND ACCESSORIES

- > Haulotte Extra Reach
- > Hydraulic generator 3.5 Kw, 6Kw and 9Kw
- > USB port
- > Large basket 2.44 x 0.91 m
- > Swing door entry gate
- > Air line to platform
- > Cold weather kit
- > Glazier kit
- > Flashing light
- > Sherpal telematics subscription
- > Non-marking tires



autovictor

 *Keep on moving to the future.*

HAULOTTE HA 20 RTJ



AUTOVICTOR s.r.l.

Via Galvani 11/13

28060 San Pietro Mosezzo - Novara

Tel. +39 0321 35000

info@autovictor.it

www.autovictor.it